

The ALBUS LED DownLight series is aesthetically designed to allow additional replacement capabilities for common downlight applications in prominent building lobbies, guest areas, galleries, etc. The matte glass finish serves to prevent glare while the polished white casing provides easy matching to ceiling colors. The ALBUS LED DownLight does not require modifications to existing sockets.



LED DownLight

Input Voltage : 110 ~ 240 VAC	Socket : Connector
Input Power : 6.5, 15, 25W	IP Protection : IP 20
Beam Angle : 120°	Color : Warm / Pure / Cool
Lifespan : > 35000 Hours	Certificate : CUL / UL / CE / GS / RoHS
Product Material : Aluminium Casing & Polycarbonate	
Product Size Availability : 4 , 6 , 8 & 10 inches	



LED Ceiling Light

Input Voltage : 90 ~ 240 VAC	Socket : Connector
Input Power : 15W	IP Protection : IP 65
Beam Angle : 15°, 25°, 45°, 120°	Color : Warm / Pure / Cool
Lifespan : > 35000 Hours	Certificate : CUL / UL / CE / GS / RoHS
Product Material : Molded Ceramic with Aluminium & Crystal Glass	



LED Ceiling Light (Multiple)

Input Voltage : 90 ~ 240 VAC	Socket : Connector
Input Power : 60W	IP Protection : IP 20
Beam Angle : 45°, 120°	Color : Warm / Pure / Cool
Lifespan : > 35000 Hours	Certificate : CUL / UL / CE / GS / RoHS
Inner Product Material : Molded Ceramic with Aluminium & Crystal Glass	
Outer Product Material : Aluminium Casing	